

In compliance with Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation - CPR) this certificate applies to the construction product

## **Festigkeitssortiertes keilgezinktes Vollholz GLT®**

according to the product specification listed in the current addendum to this certificate produced by

### **Company**

**Hasslacher Holding GmbH**

**Feistritz 1**

**AT-9751 Sachsenburg**

and produced in the manufacturing plant

**Hasslacher Preding Holzindustrie GmbH**

**Wohlsdorfer Straße 1, AT-8504 Preding**

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in

**ETA-13/0644, issued on 01.04.2019**

and

**EAD 130484-00-0304**

under system 1 for the performance set out in the ETA are applied and that the factory production control conducted by the manufacturer is assessed to ensure the constancy of performance of the construction product.

## **CERTIFICATE OF CONSTANCY OF PERFORMANCE**

**Certificate number:** 1359-CPR-0830

**Date of first issue:** 22.02.2022

**Date of issuance:** 22.02.2022

This certificate will remain valid as long as neither the ETA, the EAD, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

For the validity of this certificate see [www.holzforschung.at](http://www.holzforschung.at).



**Dr. Andreas Neumüller**  
Authorised signatory



**Dr. Manfred Brandstätter**  
Head of the Certification Body

## Addendum to certificate 1359–CPR-0830

Date of issuance: 22.02.2022

### Scope of certification for the following products:

#### **Festigkeitssortiertes keilgezinktes Vollholz GLT® – Tension proof loaded, structural finger jointed solid timber beam GLT®<sub>MONO</sub>**

Timber species/ Strength classes:	PCAB – spruce, ABAL – fir; C 24
Mechanical resistance:	according to ETA-13/0644
Services classes:	NK 1, NK 2
max. dimension:	Spruce / Fir: 140 x 240 mm <sup>2</sup>
Manufacturing of finger joints:	According to EN 15497
Finger joint profile:	15 / 3,8 / 0,42 mm
Adhesive – Finger joints:	Type I: PUR according to EN 15425
Reaction to fire	D-s2, d0
Formaldehyde class:	E1
Natural durability class:	According to EN 350-2
Applied tension stress:	50 % to 75 % of $f_{t,0,k}$
Minimum duration of applied tension stress:	≥ 1,5 seconds