

In compliance with Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation - CPR) this certificate applies to the construction product

# Structural finger jointed solid timber

according to the product specification listed in the current addendum to this certificate placed on the market

# Company HASSLACHER PREDING HOLZINDUSTRIE GMBH Wohlsdorfer Straße 1 AT-8504 Preding

and produced in the manufacturing plant

#### AT-8504 Preding, Wohlsdorfer Straße 1

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard

EN 15497:2014

under system 1 for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the constancy of performance of the construction product.

### CERTIFICATE OF CONSTANCY OF PERFORMANCE

Certificate number: 1359-CPR-0601 Date of first issue: 03.03.2015 Date of issuance: 27.02.2018

This certificate will remain valid as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

For the validity of this certificate see www.holzforschung.at.

Dr. Andreas Neumüller

Authorised signatory

Dr. Manfred Brandstätter lead of the Certification Body



## Annex to Certificate 1359-CPR-0601

Date of issue: 27.02.2018

## Scope of certification for the following products:

#### Structural finger-jointed solid timber

Timber species/strength classes:

PCAB - spruce, ABAL - fir, PNSY - pine

C 24

Services classes:

1, 2

Mechanical resistance:

according to EN 338

max. dimension:

PCAB - spruce/ ABAL - fir: 140 x 240 mm<sup>2</sup>

PNSY - pine: 80 x 240 mm<sup>2</sup>

Adhesive - Finger joints

Type I: PUR according to EN 15425

Reaction to fire:

D-s2, d0

Formaldehyde class:

E1

Natural durability class:

according to EN 350-2