

Declaration of Performance

No.: DOP_HPH_GLT_en_V2.0

1. Unique identification code of the product type:

Strength graded and finger jointed structural timber GLT[®] acc. ETA-13/0644

2. Type, batch or serial number or other identification symbol for identification of the building product in accordance with Article 11, Para. 4 of the Construction Products Directive [*BauPVo*]:

The production date or the identification number for the relevant job can be taken from the component identification.

3. Intended use of the construction product in accordance with the harmonized technical specification:

Building and bridge construction

3. Name, registered trade name or trademark in addition to manufacturer's address in accordance with Article 11, Para. 5 of the Construction Products Directive [*BauPVo*]:

**HASSLACHER PREDING Holzindustrie GmbH
Wohlsdorfer Straße 1
8504 Preding
Austria**

5. Name and address of the appointed agent for the tasks in accordance with Article 12, Para. 2 of the Construction Products Directive [*BauPVo*]:

No appointed agent

6. System for assessment and verification of constancy of performance in accordance with Annex V of the Construction Products Directive [*BauPVo*]:

System 1

7. If the construction product is regulated by a European technical assessment:

Not applicable

8. If the construction product is regulated by a harmonized standard:

The notified body Holzforschung Austria 1359 has carried out - in respect of the bond strength and fire behavior - the determination of the product type based on an initial test, the initial inspection of the plant and the in-plant production control as well as continuous monitoring, assessment and evaluation of the in-plant production control, and has issued a Certificate of Conformity with the EC Certificate of Conformity no. 1359-CPR-0674.

9. Declared performance:

Main features	Performance	Harmonized technical specification
Modulus of elasticity	Spruce/fir: C24 in accordance with EN 338	ETA-13/0644
Bending strength	Assignment of the supplied woods to strength classes can be taken from the accompanying documents.	
Compressive strength		
Tensile strength		
Shear strength	The relevant product dimensions can be taken from the accompanying documents.	
Bond strength	Finger joint adhesive type I in accordance with EN 15425 C24: 24 N/mm ² PUR adhesive in accordance with EN 15425	
Proof level	<input type="checkbox"/> $t_{proof} = 0,5 \times f_{t,0,k} \rightarrow k_{pl} = 1,0$ <input type="checkbox"/> $t_{proof} = 0,6 \times f_{t,0,k} \rightarrow k_{pl} = 1,05$ <input type="checkbox"/> $t_{proof} = 0,75 \times f_{t,0,k} \rightarrow k_{pl} = 1,10$	
Durability	in accordance with EN 350-2	
Fire behaviour Resistance to fire	D-s2, d0	
Release of hazardous substances	Formaldehyde emission class E1	



10. The performance of the product in accordance with numbers 1 and 2 corresponds to the declared performances in accordance with number 9. The manufacturer alone in accordance with number 4 is responsible for issuing this declaration of performance.

Signed on behalf of the manufacturer:

Manfred Steinwiedder / managing director HASSLACHER PREDING Holzindustrie GmbH

Name and function

HASSLACHER PREDING
 Holzindustrie GmbH
 Wohlsdorfer Straße 1 | 8504 Preding
 Austria | hasslacher.com
 T +43 3185 86 23-0 | F -15
 Ein UNTERNEHMEN der HASSLACHER Gruppe
 A MEMBER of HASSLACHER group

Preding, 2017-10-30

Place and date of issue

Stamp/signature