

## Declaration of Performance

No.: DOP\_NTC\_BSH

1. Unique product type identification code:

**Glued laminated timber NTC**

2. Intended use of the building product according to harmonized technical specification:

**Buildings and Bridges**

3. Name, registered trade name or brand, along with the address of the producer according to Article 11 Paragraph 5 construction products regulation:

**NORITEC Holzindustrie GmbH**

**Feistritz 1**

**9751 Sachsenburg**

**Austria**

4. Name and address of the authorized agent for the tasks referred to in Article 12 Paragraph 2 construction products regulation:

**No authorized agent**

5. System of assessment and verification of performance constancy pursuant to Appendix V of the construction products regulation:

**System 1**

6. If the building product is regulated by a harmonized standard:

**EN 14080:2013**

7. Notified Body(ies):

**No. 1359**

8. If the building product is regulated by an European technical assessment:

**Not applicable**

9. Declaration of performance:

Main Features and Characteristics		Performance
<b>Mechanical characteristics of glued laminated products</b>	Characteristics of timber	NPD
	Bending strength	Classification based on the characteristics of laminations according EN 338 – assignment of strength class corresponding Table 4 or 5 EN 14080
	Compression strength	
	Tensile strength	
	Shear strength	
	Modulus of elasticity	Spruce/Fir: GL20h, GL24h, GL24c, GL28h, GL28c, GL30h, GL30c, GL32h, GL32c
	Bonding strength	
	Strength of finger joints	Pine, Larch: GL24h, GL24c, GL28c, GL30h
	Additional for glued laminated timber with large finger joints: Bending strength of large finger joints	NPD
Geometrical data	NPD	
<b>Resistance to fire</b>		NPD
<b>Bonding strength</b>	Glue line integrity of surface bonding	Delamination test according EN 14080, Annex C, Test method B
	Glue lines between components of glued laminated timber	NPD
	Large finger joints	NPD
<b>Reaction to fire</b>		D-s2, d0
<b>Emission of formaldehyde</b>		E1
<b>Release of other dangerous substances</b>		NPD
<b>Durability of bonding strength</b>	Species	Spruce/Fir, Pine, Larch
	Adhesives	MUF / Type I according EN 301 I 90 FJ 0,1 S I 90 GP 0,3 S
<b>Durability against biological attack</b>	Lamination without preservative treatment	Durability class 5 according EN 350-2
	Lamination with preservative treatment	NPD

NPD – No Performance Determined

**NORITEC Holzindustrie GmbH**  
Feistritz 1 | 9751 Sachsenburg | Austria  
T +43 4769 22 49-0 | F +43 4769 22 49-129  
info@hasslacher.com | [hasslacher.com](http://hasslacher.com)

**HASSLACHER**  
**NORICA TIMBER**  
From **wood** to **wonders**.

10. The performance of the previous product corresponds with the declared performance/the declared performances. For the creation of this performance in accordance with the EU regulation No. 305/2011 the manufacturer is uniquely responsible for.

Signed in the name of the manufacturer:

Gerhard Göritzer / managing director NORITEC Holzindustrie GmbH

Name and position

**NORITEC**  
**Holzindustrie GmbH**  
9751 Sachsenburg - Feistritz 1  
AUSTRIA - [www.hasslacher.at](http://www.hasslacher.at)  
T +43 4769 2249 236  
Ein Unternehmen der HASSLACHER NORICA TIMBER Gruppe  
A company of the HASSLACHER NORICA TIMBER Group

**HASSLACHER**  
**NORICA TIMBER**

Sachsenburg, 26th June 2019

Place and date of issue

Stamp/signature