

In compliance with Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation - CPR) this certificate applies to the construction product

## **HASSLACHER CROSS LAMINATED TIMBER**

according to the product specification listed in the current addendum to this certificate placed on the market by

### **Company**

**HASSLACHER HOLDING GMBH**

**Feistritz 1**

**AT-9751 Sachsenburg**

and produced in the manufacturing plant

**Nordlam GmbH, Gasereistraße 1, DE-39126 Magdeburg**

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in

**ETA-12/0281, issued on 09.11.2020**

and

**EAD 130005-00-0304**

under system 1 for the performance set out in the ETA are applied and that the factory production control conducted by the manufacturer is assessed to ensure the constancy of performance of the construction product.

## **CERTIFICATE OF CONSTANCY OF PERFORMANCE**



**Certificate number:** 1359-CPR-0815

**Date of first issue:** 23.02.2021


**Date of issuance:** 30.08.2022

This certificate will remain valid as long as neither the ETA, the EAD, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

For the validity of this certificate see [www.holzforschung.at](http://www.holzforschung.at).



**Dr. Andreas Neumüller**  
Authorised signatory



**Dr. Manfred Brandstätter**  
Head of the Certification Body

# Addendum to certificate 1359-CPR-0815

Date of issuance: 30.08.2022

## Scope of certification:

### HASSLACHER CROSS LAMINATED TIMBER

#### Solid wood slabs to be used as structural elements in building

Structure:	minimum 3 layers, layers arranged perpendicular (angle of 90°), maximum 11 layers, symmetrical construction
Thickness:	60 - 280 mm
Width x length (w × l):	max. 1,25 x 24,0 m
Service classes:	1, 2
Wood species:	PCAB – spruce / ABAL – fir
Strength classes:	Strength classes of the laminations C24/T14 Strength classes of the laminations
- CL26E11.8	- Outer layers C40/T26
- CL36E14.7	- Inner layers C24/T14
Adhesive:	
- Finger joints	Type I: MUF according to EN 301 I 90 FJ 0,1 S
- Surface bonding	Type I: MUF according to EN 301 I 90 GP 0,3 S