

In compliance with Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation - CPR) this certificate applies to the construction product

HASSLACHER CROSS LAMINATED TIMBER

according to the product specification listed in the current addendum to this certificate placed on the market by

Company
HASSLACHER HOLDING GMBH
Festritz 1
AT-9751 Sachsenburg

and produced in the manufacturing plant

Noritec Holzindustrie GmbH Latzendorf 100 AT-9832

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in

ETA-12/0281, issued on 09.11.2020

EAD 130005-00-0304

under system 1 for the performance set out in the ETA are applied and that the factory production control conducted by the manufacturer is assessed to ensure the constancy of performance of the construction product.

CERTIFICATE OF CONSTANCY OF PERFORMANCE

Certificate number: 1359-CPR-0734 Date of first issue: 22.08.2017 Date of issuance: 06.03.2024

This certificate will remain valid as long as neither the ETA, the EAD, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

For the validity of this certificate see www.holzforschung.at.

Dr. Andreas Neumüller

Authorised signatory

PD Gerhard Grüll
Head of the Certification Body

HOLZFORSCHUNG AUSTRIA - ÖSTERREICHISCHE GESELLSCHAFT FÜR HOLZFORSCHUNG ZVR 850936522 A-1030 Wien, Franz-Grill-Straße 7 Tel +43-1/798 26 23-0 Fax +43-1/798 26 23-50 hfa@holzforschung.at www.holzforschung.at

Addendum to certificate 1359-CPR-0734

Date of issuance: 06.03.2024



Scope of certification:

HASSLACHER CROSS LAMINATED TIMBER Solid wood slabs to be used as structural elements in building

Structure:

minimum 3 layers,

layers arranged perpendicular (angle of 90°),

maximum 11 layers, symmetrical construction

Element thickness:

57 - 360 mm

Element size (w × I):

max. 4,0 × 20,0 m

Use classes:

1, 2

Species:

PCAB - Spruce / ABAL - Fir

PNSY - Pine

LADC - Larch

Strength classes

- CL26E11.8

C24/T14

- CL36E14.7

C24/T14 for inner layer

C40/T26 for cover layer

Adhesive finger joints:

Type I: MUF according to EN 301

Adhesive face bonding:

Type I: MUF according to EN 301