



Entwicklungs- und Prüflabor  
Holztechnologie GmbH

Zellescher Weg 24 · D-01217 Dresden  
www.eph-dresden.de



Deutsche  
Akkreditierungsstelle  
D-PL-11054-01-00  
D-ZE-11054-01-00

accredited by Deutsche Akkreditierungsstelle GmbH (DAkkS)

# T E S T C E R T I F I C A T E

CT-14-01-27-01

**Product:** Cross laminated timber  
Thickness: 95 mm  
Resin: Prefere 4546  
Hardener: Prefere 5093  
Mixing ratio: 100 : 50  
Date production: 2013-06-26

**Company:** Dynea AS,  
P.O. Box 160  
Svelleveien 33  
2001 Lillestrøm - Norway

**Order:** Determination of the formaldehyde release of cross laminated timber according to prEN 16351:2011-12 „Wood constructions - Cross laminated timber - Requirements“


**Test method:** Chamber method DIN EN 717-1  
Chemical analysis formaldehyde: acetyl acetone - method


**Test report:** Test report 2513316 dated August 13<sup>th</sup>, 2013

**Test result:** The formaldehyde release of the above mentioned test material is 0.03 ppm (432 h).  
The tested cross laminated timber board fulfils the requirements of the prEN 16351:2011-12 „Wood constructions - Cross laminated timber - Requirements“ Appendix A; Table A1 regarding the formaldehyde release and meets the requirements of formaldehyde-class E1

Dresden, January 27<sup>th</sup>, 2014



  
Head of laboratory

  
Engineer in charge